



QC4-BH and QC7I-MH Water Filters for Coffee Makers

9272-00 • 9272-41 • 9613-01

Premium quality water that results in better tasting hot beverages and reduced machine maintenance

BENEFITS

- Removes chlorine and other off-tastes and odors
- Exclusive Precoat technology filters out dirt down to 1/2 micron in size
- Self-contained scale inhibitor feed inhibits costly mineral scale build-up
- Increases energy efficiency
- Increases holding time
- Increases brewer life – reduces corrosion
- NSF Standards 42 and 53 listed



QC4-BH APPLICATION/SIZING
For smaller plumbed in coffee brewers
with a flow rate of .5 gpm or less.
1,500 gallon capacity

QC7I-MH APPLICATION/SIZING
For urns and larger plumbed in brewers
with flow rates above .5 gpm.
9,000 gallon capacity

QC4-BH Filter: 9272-00
BH Cartridge: 9612-00

QC7I-MH Head: 9272-41
MH Cartridge: 9613-01

Note: Head and Cartridge
sold separately

INSTALLATION TIPS

- Never use saddle valve for connection
- QC4-BH: Use minimum 1/4" water line
- QC7I-MH: Use minimum 3/8" water line
- **Flush cartridge by running two gallons through machine at full flow**

OPERATION TIPS

- Change cartridges:
 - on a regular 6 month preventative maintenance program
 - when the pressure gauge indicates a pressure less than 10 psi *when the system is operating* or at least

Always flush the filter cartridges when changing



SPECIFICATIONS

Dimensions: 16"H x 5"W x 5"D
 Inlet connection: 1/4"
 Service flow rate: Minimum .1 gpm
 Maximum .5 gpm
 Pressure: Minimum 10 psi
 Maximum 125 psi (non-shock)
 Maximum temperature: 100°F (38°C)
 No electrical connection required
 Shipping weight: 4 lbs.
 Operating weight: 9 lbs.




SPECIFICATIONS

Dimensions: 29"H x 5-1/2"W x 5"D
 ("H" dimension includes 2-1/2"
 clearance for cartridge changing)
 Minimum inlet connection: 3/8" OD
 Service flow rate: Minimum .5 gpm
 Maximum 1.67 gpm
 Working pressure: 10-125 psi, non-shock
 Maximum temperature: 100°F (38°C)
 No electrical connection required
 Shipping weight: 8 lbs.
 Operating weight: 14 lbs.

LIMITED WARRANTY OF PHYSICAL QUALITY

If, within eighteen months after manufacture or twelve months after purchase (whichever occurs first), any part of Everpure, Inc. manufacture which is returned to its factory, shipping charges prepaid, is found to be defective in material or workmanship in the judgement of Everpure's engineers, Everpure, Inc. will repair or replace such part at no charge, f.o.b., Westmont factory. Everpure, Inc. however, shall not be liable for damages or delays caused by any defective material or workmanship, or by failure of any parts due to normal wear and tear. Everpure, Inc. will not be responsible for products which malfunction due to user neglect or unauthorized modification.
 NOTE: Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. Similarly, some states do not allow the exclusion or limitation of consequential or incidental damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights which may vary from state to state.



System Tested and Certified by NSF International against ANSI/NSF Standard 42 and 53 for the reduction of:

- Standard No. 42: Aesthetic Effects
 - Chemical Unit
 - Taste and Odor Reduction
 - Chloramine Reduction
 - Chlorine Reduction, Class I
 - Mechanical Filtration Unit
 - Particulate Reduction, Class I: 99.9+% reduction of particles one-half micron and larger in size
- Standard No. 53: Health Effects
 - Mechanical Filtration Unit
 - Turbidity Reduction
 - Cyst Reduction
 - Asbestos Reduction

Check for compliance with state and local laws and regulations. Do not use where the water is microbiologically unsafe, or with waters of unknown quality without adequate disinfection before or after the unit. May be used with disinfected water where filterable cysts may be present.



EVERPURE, INC.
 660 Blackhawk Drive
 Westmont, IL 60559-9005
 Tel (630) 654-4000
 FAX (630) 654-1115
 Technical Service
 (800) 942-1153
<http://www.everpure.com>

In Europe:
N.V. EVERPURE (EUROPE)
S.A.
 Research Park, Haasrode
 B-3001 Heverlee
 Belgium
 Tel 32-16-401191
 FAX 32-16-402691

In Japan:
EVERPURE JAPAN, INC.
 1-8-19, Tsumada Kita,
 Atsugi-Shi
 Kanagawa 243
 Japan
 Tel 81-462 (23) 6563
 FAX 81-462 (21) 6775

Distributor in Canada:
DANAMARK, LTD.
 135 Nuggett Court
 Brampton, Ontario
 Canada L6T 5H4
 Tel (905) 792-2353
 (800) 268-5967
 FAX (905) 792-2986